

3-Strip Longstrip

21 mm tongue/groove

Technical information	
Produced according to:	European parquet norm EN 13489 - 2017
Dimension:	21 x 215 x 2200 mm
Toplayer:	about 5.5 mm
Construction:	3-layer construction; Hardwood toplayer, middlelayer and bottomlayer made of spruce Toplayer about 5.5 mm Middlelayer 10.5 mm Bottomlayer 5.0 mm
Boards/ m ² per carton:	4/ 1.89
Cartons/ m ² per pallet:	50/ 94.5
Slotted top layers per carton:	max. 1
Weight per carton/ pallet in kg:	22/ 1100
Floor heating systems:	Suitable
Fire behavior ¹⁾ :	Cfl-s1 and Dfl-s1 depending on wood specie and surface treatment
Content of formaldehyd ²⁾ :	E1
Content of pentachlorphenol (PCP) ²⁾ :	no performance detected
Density kg/ m ³ ²⁾ :	about 600
Antislip performance:	Live Matt: USRV 29, R9 ³⁾ Sport lacquer T79: Coefficient of friction: 80-110 ⁴⁾ Dynamic coefficient of friction: 0.4-0.6 ⁴⁾
Thermal conductivity ²⁾ :	0.20 W/ (m·K)
Areal thermal resistance ⁵⁾ :	0.15 m ² · K/ W



Toplayer: Hardwood
 Middlelayer: Spruce
 Bottomlayer: Spruce

DOP 4658



BOEN AS
 EN 14342



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to CEN/TS 15676,

⁴⁾ according to EN14904, ⁵⁾ according to EN 12524