



**BOEN**  
SPORT

# 3-Strip Longstrip

## 23 mm tongue/groove

Technical information	
Produced according to:	European parquet norm EN 13489 - 2017
Dimension:	23 x 215 x 2200 mm
Toplayer:	about 3.5 mm
Construction:	3-layer construction; Hardwood toplayer, middlelayer and bottomlayer made of spruce Toplayer about 3.5 mm Middlelayer 11.5 mm Bottomlayer 8.0 mm
Boards/ m <sup>2</sup> per carton:	4/ 1.89
Cartons/ m <sup>2</sup> per pallet:	45/85.05
Slotted top layers per carton:	max. 1
Weight per carton/ pallet in kg:	23/ 1050
Floor heating systems:	Suitable
Fire behavior <sup>1)</sup> :	Cfl-s1 and Dfl-s1 depending on wood specie and surface treatment
Content of formaldehyd <sup>2)</sup> :	E1
Content of pentachlorphenol (PCP) <sup>2)</sup> :	no performance detected
Density kg/ m <sup>3</sup> <sup>2)</sup> :	about 600
Antislip performance:	Live Matt: URSV 29 <sup>3)</sup> , R9 Sport lacquer T79: Coefficient of friction: 80-110 <sup>4)</sup> Dynamic coefficient of friction: 0.4-0.6 <sup>4)</sup>
Thermal conductivity <sup>2)</sup> :	0.21 W/ (m·K)
Areal thermal resistance <sup>5)</sup> :	0.16 m <sup>2</sup> · K/ W



DOP 4658



**BOEN AS**  
EN 14342



<sup>1)</sup> according to DIN EN 13501-1, <sup>2)</sup> according to DIN 14342, <sup>3)</sup> according to CEN/TS 15676,

<sup>4)</sup> according to EN 14904, <sup>5)</sup> according to EN 12524